



*Heatsink and CPU fan type selection is dependent on CPU speed and environment based on customer product application.

High Efficiency CPU!

Intel Pentium M achieves high performance with very low power consumption.

Best fit for compact and quiet products!

Since FAN-less CPU can be used, it can contribute to compact and quiet product.

A variety of Graphic functions!

It also has an AGP (includes ADD) slot and LVDS interface in addition to a graphic function from built-in chip set, and a variety of graphic functions can be used.

Advanced Interface!

It has advanced interfaces such as PCI-X and Serial ATA. Moreover, it also has the 4 channels of serial port that embedded system often demands.

Environmentally Friendly!

Lead free solder is proactively used for reduction to environmental impact.

Contact _____

Ricoh Electronics, Inc.

TEL: 714-566-2500 FAX: 714-566-3250

E-mail : Nguyen_Quach@rei.ricoh.com (USA) or fbx@ricoh.co.jp (Japan)

Web: http://www.rei.ricoh.com/scu_main.html

Specification*1

<i>Chipset</i>		Intel 855GME
<i>Memory</i>	Type	DDR266/333
	Module	PC2100/2700
	Registered/Unbuffered	Unbuffered
	ECC	Yes
	CL	2/2.5
	Number of Socket	2 Sockets
	Max capacity	2GB
<i>Video</i>		Built in chipset
<i>Audio</i>		AC'97 On Board
<i>LAN</i>		10/100BASE-TX Onboard
<i>External Interface</i>	USB	2ports (USB2.0)
	Analog RGB	1port
	Serial	1port
	Parallel	1port
	PS/2	Keyboard, Mouse
	Audio	Line-IN, Line-OUT, Mic-IN
	LAN	1port
<i>Internal Interface</i>	PCI Slot	2slots
	PCI-X Slot	1slot
	AGP Slot	1slot
	IDE	2ch
	FDD	1ch
	USB Header	2ports (USB2.0)
	Serial Header	3ports
	Serial ATA	2ports
	FAN	CPU, CASE, PSU
	LVDS	1port
<i>Supported Operating Systems</i>		Windows2000 Professional WindowsXP Professional
<i>FormFactor</i>		Micro ATX 238mm x 225mm

*1: Specification is subject to change without notice

*2: uFC-BGA CPU is mounted to board directly (Socket model available)